

Project:

Location:

Cat.No:

Notes:

# **BASeries** 2'x2' Commercial/Industrial Grade Highbay 10,000-19,500 Lumens

#### **Product Description**

The BA Series 2'x2' fixture is precision-engineered for expansive illumination with a wide 120-degree distribution angle, making it ideal for applications requiring broad coverage. Designed for mid to high ceilings, it offers versatility with various lumen packages and mounting options. Its robust thermal design ensures reliable performance in challenging conditions, suitable for installation heights from 15 to 30 feet. Handcrafted in Ontario, Canada, it's the ideal choice for your lighting needs.

#### Application

This unit is a great option for industrial, commercial or agricultural buildings such as metal fabricating shops, woodworking shops, storage sheds, warehouses, drive sheds, on farm shop's, grocery stores, tool stores, airplane hangers, hockey rinks, hobby shops and many more. Reccomended Installation Height Is 15 to 30 Feet.

#### Features

- Configurations exceeding 160 lm/w
- Slim profile 1.75" thick for tight fit spaces
- Standard 0-10V dimming for control/precision
- Robust LED boards made in house by JW LED Inc.

#### Options


- Wide range of lumen outputs
- Variety of motion sensors or controls
- Customizable color temperature or CRI values
- Pre-wired whips for quick installation


#### Mounting

- Surface mount (This unit can be mounted directly to any ceiling or wall)
- Suspension mount (Add the chain hangers in the ordering code)


#### Approvals

Approved for use in Canada and USA, QPS Certified













#### Warranty

Standard 5 year warranty, view our warranty policy for full details

Knockout For Back Acess Wiring











## **Ordering Guide**

## Example:BA22-8C50K195L-UNVD1NW-NLSM

BA22 -	CRI	ССТ	Lumens	_	Voltage	Driver	0-10V Wiring	_	Lens	Mounting	Options
	<b>8C</b> 80 <b>9C</b> 90	30K3000K40K4000K50K5000K65K6500K	<b>195L</b> 19,500 Lumens <b>184L</b> 18,400 Lumens <b>137L</b> 13,700 Lumens <b>100L</b> 10,000 Lumens		<b>UNV</b> 120-277V <b>347</b> 347V	<b>D1</b> 0-10V 1%	<i>NW</i> Not Wired for DIM <i>PW</i> Pre-Wrired for DIM		<ul><li><i>NL</i> No Lens</li><li><i>FS</i> Frosted Smooth</li></ul>	<i>SM</i> Surface Mount <i>CH</i> Chain Hanger Hooks	BlankNoneRTPRetail PackagingCD33' Whip Pre-Wired (Black)MS5Motion Sensor for AislewayMS4Motion Sensor for 360°4,5

### Accesories



Order Code: HDW0001

Chain hanger hook for quick chain connect

#### Order Code: LNS0009

Frosted smooth acrylic lens diffuser

## Specification Chart

Lumens	Watts	Color	CRI
19,500	122	5000K	80
18,400	113	5000K	80
13,700	84	5000K	80
10,000	61	5000K	80

Testing is based on ambient 25c. As nominal calculations, actual outputs may vary based on product configurations. We reserve the right to correct any printing errors or mistakes in our tables