



WL Series

Winglight 4 Foot Narrow Body Vaportight

2,000 - 8,000 Lumens



Project:

Location:

Cat.No:

Notes:

Product Description

The Winglight Series is the culmination of extensive research and development in poultry lighting, providing flicker-free illumination with smooth, seamless dimming controlled by a 0-10V signal. The advanced internal circuitry ensures a flawless transition from darkness to light. With various color options and lumen outputs available, the Winglight is designed to enhance poultry performance according to your needs. Additionally, our 0-10V Bridge Controller allows easy integration with any poultry system that uses a 0-10V control signal, ensuring compatibility and precise control for optimal lighting results.

Application

This unit is designed to integrate seamlessly with our 0-10V Winglight Bridge Control, providing a smooth dimming experience with precise control. It’s ideal for poultry applications that require accurate and reliable lighting adjustments.

Features

- Flicker free design tested by poultry experts
- Winglight source to sink control compatible
- 0.1% - 100% 0-10V dimming for control/precision
- Control up to 4 seperate zones with 250-300 lights max per zone
- Compatible with any poultry control that has a 0-10V control signal

Options

- Wide range of lumen outputs
- Variety of lens option’s
- Customizable color temperature or CRI values
- POM or stainless latch options

Mounting


- Surface mount (This unit can be mounted directly to any ceiling or wall)
- Suspension mount (Chain mounting compatible by default)

Approvals


Approved for use in Canada and USA, QPS Certified, NSF Rated Components, Neema 4x rated

Warranty

Standard 5 year warranty, view our warranty policy for full details



NEMA 4X



Ordering Guide

Example:WLN4-8C40K055L-UNVD1NW-FRPMMB

| WLN4 | CRI | CCT | Lumens | Voltage | Driver | 0-10V Wiring | Lens | Latches | Mounting |
|--|----------------|--|--|--------------|-----------------------|----------------------|--|--|--|
| | 8C 80 9C 90 | 30K 3000K 40K 4000K 50K 5000K 65K 6500K | 080L 8,000 Lumens 055L 5,500 Lumens 040L 4,000 Lumens 020L 2,000 Lumens | UNV 120-277V | D1 0-10V 0.1% Dim. | PW Pre-Wired for DIM | CR Clear Ribbed FR Frosted Ribbed CS Clear Smooth FS Frosted Smooth | PM POM (Nylon Latches) SS Stainless Steel Latches | MB Surface/Chain Mount Brackets NM No Mount Bracket’s |
| <div>Options</div> <div>Blank None CD2 2’ Whip Pre-Wired (Black) CD3 3’ Whip Pre-Wired (Black)</div> | | | | | | | | | |

Specification Chart

| Lumens | Watts | Color | CRI |
|--------|-------|-------|-----|
| 8,000 | 56 | 5000K | 80 |
| 5,500 | 37 | 5000K | 80 |
| 4,000 | 27 | 5000K | 80 |
| 2,000 | 14 | 5000K | 80 |

Testing is based on ambient 25c. As nominal calculations, actual outputs may vary based on product configurations. We reserve the right to correct any printing errors or mistakes in our tables

